

High Bay IP65

Features:

- Square profiled aluminum housing concealed with two extruded welding side covers for high IP rating
- Anodized aluminum reflector and clear tempered glass cover are designed to optimize light distribution
- Gas-tight silicon rubber seal made for wet locations
- Mounting: suspended by poles or well/surface mount

Lamp and ballast:


- 400W square tubular with high lighting efficacy at rated 80,000hrs lifetime, about 20 years burning on 4000hrs/year
- Electronic ballast features high power factor (>0.95), flicker-free light, constant output wattage, and safe protection

Ambient temperature for lighting fixture:

-20°C ~ 40°C

Applications:

Tunnels, bridges, highways, airports, stadiums



Type	Lamp	PSU Frequency (Hz)	Voltage (V)	Current (A)	IP
High Bay IP65	100W Square Tubular	50/60	120/220/277	0.93 ~ 0.42	43
High Bay IP65	150W Square Tubular	50/60	120/220/277	1.35 ~ 0.61	43
High Bay IP65	200W Square Tubular	50/60	120/220/277	1.77 ~ 0.80	43
High Bay IP65	250W Square Tubular	50/60	120/220/277	2.21 ~ 1.00	43
High Bay IP65	400W Square Tubular	50/60	120/220/277	3.54 ~ 1.60	43