

Aqua 1



- Soft arc linear lens diffuser designed to provide maximum spacings between emergency luminaires
- Fully Compact polycarbonate enclosure and screw-fixing diffuser located with brass threaded inserts
- Hinged steel gear tray, centre rear BESA entry and 20mm conduit knockouts at each end for ease of installation
- Fluorescent versions supplied complete with lamp
- Can be fitted with a self-adhesive legend kit to create an exit sign
- Non-maintained versions are BSI Kitemarked
- Ideal for use in corridors, exits and escape routes

Order Guide

Product Code	Description	Lumens	Weight
AQ1/8/NM3/E	8w non-maintained, economy	80	1.5kg
AQ1/8/NM3	8w non-maintained	120	1.5kg
AQ1/8/NM3/H	8w non-maintained, high output	180	1.5kg
AQ1/8/M3/E	8w maintained, economy	80	1.5kg
AQ1/8/M3	8w maintained	120	1.5kg
AQ1/8/M3/H	8w maintained, high output	180	1.5kg
AQ1/28/NM3	2x8w non-maintained	150	1.5kg
AQ1/28/NM3/H	2x8w non-maintained, high output	250	1.5kg
AQ1/LE/M3	LED maintained	120	1.5kg
.../SRW	Semi recess kit, white trim		
.../LK	Self adhesive legend		
.../AD	Intelligent addressable luminaire		
.../DD	DALI dimmable control gear		
.../HF	High frequency gear		
.../OP	Opal Diffuser		
.../ST	Digital self-test		
.../PT	Push-to-test switch		
.../V	Anti-tamper screws		

Luminaire Dimension

Length 350mm

Width 108mm

Depth 80mm

Cut-Out Dimension

Length 330mm x Width 90mm

(when used with /SRW

semi-recess kit)

Viewing Distance

18 Metres

(when used with LK self

Adhesive legend)