

EcoSTAR® Halo 80



Specifically designed for use with LED technology, EcoSTAR® Halo is a range of classically styled recessed downlights for a variety of commercial applications

- Discreet minimal bezel, 85mm dia., die-cast from pure aluminium
- Matt black darklight baffle, developed to minimise glare
- Sealed to IP44 from below
- Excellent efficacy to aid Part L compliance
- Thermally optimised 24 super-fin die-cast heatsink
- Precision moulded polycarbonate reflector with medium beam distribution

Order Guide

Product Code	Optic	Power (w)	Dia (mm)	Cut-Out (mm)	Depth (mm)
ES650H08B	White trim, black baffle	7.9	85	81	95
ES1200H08B	White trim, black baffle	15.1	85	81	95
ES650H08W	White trim, white baffle	7.9	85	81	95
ES1200H08W	White trim, white baffle	15.1	85	81	95

Accessories

Code	Description
.../DD	DALI dimming
.../DS	DSI dimming

LED Performance

Product Code	Projected Life To L70/B50	CCT (K)	Power (w)	Luminaire Lumens	l/cw	CRI
ES650H08W	50,000 hours	4000	7.9	524	66.3	>80
ES1200H08W	50,000 hours	4000	15.1	836	55.4	>80

Photometric Data

