

# Solo



- 50mm diameter
- Superbly designed refractor lens assembly
- Emergency packs can easily pass through a 40mm ceiling cut-out
- Available with open area or escape route optics
- LED life exceeds 50,000 hours
- LED self-test versions available
- Ideal for use in hotels, retail outlets and reception areas
- Specially developed LED driver and advanced thermal engineering techniques reduce LED operating temperatures

## Order Guide

Product Code	Description	Lumens	Weight	Luminaire Dimension
SL/3NM3OA	3w LED, non-maintained, open area	75	0.1kg	Ø 50mm
SL/3NM3ER	3w LED, non-maintained, escape route	75	0.1kg	Depth 32mm
SL/3NM3OA/H	3w LED, non-maintained, open area, high output	120	0.1kg	(22mm above ceiling)
SL/3NM3ER/H	3w LED, non-maintained, escape route, high output	120	0.1kg	Emergency pack dimensions
SL/3M3OA	3w LED, maintained, open area	75	0.1kg	Ø 35mm
SL/3M3ER	3w LED, maintained, escape route	75	0.1kg	Length 190mm
SL/3M3OA/H	3w LED, maintained, open area, high output	120	0.1kg	Cut-Out Dimensions
SL/3M3ER/H	3w LED, maintained, escape route, high output			Ø 40mm
.../AD	Intelligent addressable luminaire			
.../ST	Digital self-test (not available with high output models)			

## Photometric Data

